

**TECHNICAL SHEET**

CODE:

DATE:

REV.:

SERIES: MOBILE**MODEL: P E.25**

Hourly Production	25 Mc/h
Number of bins	4 squared
Storage Capacity	35 mc
Mixer Turbo TTM soft yield	TTM 1100/ 600 lts

📖 Description of the basic machine :

N.1 AGGREGATES GROUP type BX 4.10, galvanized :

- N.1 Main body divided into 4 bins ; 2 bins on one side + 2 bins on the opposite side with a total storage capacity of 35 mc ; thickness 3 mm.
- Aggregates loading by double ramp
- N.4 unloading cones 4 mm with 1 pneumatic cylinder each one
- N.1 Electrical vibrator for sand hopper
- N.1 Extracting belt width 800 mm / length 6.200 mm / capacity 310 mc/h
- N.1 Compressor with tank 500 lts /4 kw
- N.1 Weighting hopper thickness 3 mm with 1 electrical vibrator
- N.1 Weight system kg 2.000 with 4 cells, CE

N.1 Mixing Group model TTM 1100 SKIP yield 600/500 lts

- Mixer mod. TTM 1100
- Support structure for mixer by « Balcony » with service platform and ladder
- N.1 Liter counter 1 ½ ”
- N.1 Cement weighting hopper 500 kgs with 1 cell

N.1 Control Group with :

- Control cabin 1.400 x 2.500 mm
- Control board « électromécanique »
- Software PLC Betoncontrol

N.1 Supplied Documentation :

- CE
- Handbook in mother tongue (English)
- Drawings and foundations

Options :

- Kit accessories for cement silos
- Cement Silos diam. 2400 mm up to 60 Tonnes
- Cement Silos diam. 3500 sectors made up to 120 Tonnes
- Additive dosing system by weight
- Moisture control probe
- Software PC

