

**TECHNICAL SHEET**

CODE:

DATE:

REV.:

**SERIES: MOBILE****MODEL: P E.55**

Hourly Production	55 Mc/h
Number of bins	4 squared
Storage Capacity	35 mc
Mixer Turbo TTM soft yield	TTM 2100/ 1.500 lts

📖 Description of the basic machine :

**N.1 AGGREGATES GROUP type BX 4.10, galvanized :**

- N.1 Main body divided into 4 bins ; 2 bins on one side + 2 bins on the opposite side with a total storage capacity of 35 mc ; thickness 3 mm.
- Aggregates loading by double ramp
- N.4 unloading cones 4 mm with 1 pneumatic cylinder each one
- N.1 Electrical vibrator for sand hopper
- N.1 Extracting belt width 800 mm / length 6.200 mm / capacity 310 mc/h
- N.1 Compressor with tank 500 lts /4 kw
- N.1 Weighting hopper thickness 3 mm with 1 electrical vibrator
- N.1 Weight system kg 2.000 with 4 cells, CE

**N.1 Mixing Group model TTM 2100 SKIP yield 1.500/1.200 lts**

- Mixer mod. TTM 2100
- Support structure for mixer by « Balcony » with service platform and ladder
- Water batching by weight + N.1 Liter counter 1 1/2"
- N.1 Cement weighting hopper 600 kgs with 1 cell

**N.1 Control Group with :**

- Control cabin 1.400 x 2.500 mm
- Control board « électromécanique »
- Software PLC Betoncontrol

**N.1 Supplied Documentation :**

- CE
- Handbook in mother tongue ( English )
- Drawings and foundations

Options :

- Kit accessories for cement silos
- Cement Silos diam. 2400 mm up to 60 Tonnes
- Cement Silos diam. 3500 sectors made up to 120 Tonnes
- Additive dosing system by weight
- Moisture control probe
- Software PC

